

## High capacity tank with collapsible structure

The tank is suitable, for example, for helicopter firefighting using the bambi bucket or for repumping materials at places difficult to reach.



- Rapid assembly
- Low weight
- Simple and robust structure is made of a light alloy and stainless steel
- Packed construction takes minimal space
- Volume of 1 321–13 208 gallons



Utility water reservoir or a collection tank for hazardous substances
















Process of tank draining so

Ball valve



Accessory: fill elbow as there remains no water











## **Technical details**

The tank is made of a highly resistant PES/PVC material providing the temperature range of use of -22 °F to +158 °F. The material is resistant against chemical and oil substances (see Chemical resistance certificate in the relevant chapter at the end of catalog), thereby providing enhanced potential of use in environmental accidents. The tank can be filled very quickly using the filling elbow in the upper part of the structure. A fill/discharge valve (type according to customer's choice) is located in the bottom part of the tank. As an optional accessory, the tank structure can be equipped with a holder of ferrule of fire hose. It is an above-standard construction designed especially for the purpose of firmly anchoring the position of the ball valve with the valve at the bottom of the tank. Thanks to this element, there is no danger of coming out of the holder of ferrule of fire hose of the tank tarpaulin even at full load. In order to increase the life and the resistance of the tanks we recommend using the protective pad which is a standard part of the product. The maximum slope of the tank is 8 %!

Fastening lugs are used to tighten and unfold the bottom of the tank; the structure can be anchored through openings in the footing part

Туре	ET TANK 5000	ET TANK 7500	ET TANK 20000	ET TANK 35000	ET TANK 50000
Volume (gal)	1321	1981	5283	9246	13 208
Diameter (in)	91	106	165	217	260
Height (in)	51	51	59	59	59
Vertical supports/load-bearing legs	6/2	6/2	10/4	12/4	12/4
Package dimensions (in) and weight of the structure (lb)	12 × 8 × 53 66	12 × 8 × 63 66	20 × 12 × 61 110	20 × 12 × 61 132	20 × 12 × 67 154
Package dimensions (in) and weight of the foil (lb)	12 × 5 × 32 44	12 × 5 × 32 55	16 × 16 × 39 110	24 × 16 × 43 154	32 × 20 × 47 198
Standard accessories					
Transport bag for tank	yes	yes	yes	yes	yes
Transport bag for support structure	yes	yes	yes	yes	yes
Protective pad (in)	98 × 98	118 × 118	174 × 174	236 × 236	276 × 276
Optional accessories at extra cost					
Fill elbow C52/B75/other	yes	yes	yes	yes	yes
Ball valve C52/B75/other	yes	yes	yes	yes	yes
Reduction coupling C52/B75/other	yes	yes	yes	yes	yes
Holder of ferrule of fire hose	yes	yes	yes	yes	yes